

# SAF-T-LOK

International Corporation

Material Safety Data Sheet

**PEN-OIL**

Issue Date: 19/11/2007

## SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: POA-12 PEN-OIL  
Product Type: Lubricant  
Part Numbers: **85056**  
Hazard Rating: Health: 1 Fire: 4 Reactivity: 0

Company Identification: SAF-T-LOK International Corporation  
300 EISENHOWER LANE NORTH  
LOMBARD, IL 60148

Contact: Helen Sherry  
Telephone/ Fax: (630) 495-2001  
Emergency Phone (24 Hour): (703) 527-3887  
Chemtrec (24 Hour): (800) 424-9300  
Preparer: Ind. Hygiene Department  
Internet: www.saftlok.com

Product Class: Mixture  
DOT Hazard Class: Aerosols  
Shipping Name: Flammable Gas

## SECTION II - INGREDIENT AND HAZARD INFORMATION

Components	CAS#	OSHA PEL	ACGIH TLV	Percent
Mineral Spirits	8052-41-3	100 ppm	100 ppm	50
Petroleum Oil	64742-52-5	5.0 mg/ m3		18
Petroleum distillate	64741-44-2	400 ppm	200 ppm	10
Carbon Dioxide	124-38-91000	5000 ppm	3	

## SECTION III - HAZARD IDENTIFICATION AND EMERGENCY OVERVIEW

### EMERGENCY OVERVIEW

Physical appearance: Aerosol

HMIS

Health: 1  
Flammability: 4  
Reactivity: 0  
Personal Protection: B

**WARNING;** MAY CAUSE: EYE IRRITATION  
SKIN IRRITATION  
RESPIRATORY TRACT IRRITATION  
MAY IRRITATE EXISTING ALLERGIC SKIN CONDITIONS

Relative routes of entry: Skin, Inhalation, Eyes

Skin Contact: Contact may dry the skin, prolonged contact may cause moderate irritation. Not easily absorbed.

Eye Contact: Liquid, aerosols, and vapors of this product can cause moderate to severe irritation.

Page 1 of 3

Product: POA-12

Respiratory/ Inhalation: May cause respiratory irritation, headache, nausea, fatigue, drowsiness, or impaired co-ordination.

Ingestion: Not a likely route of exposure.

Medical conditions generally aggravated by exposure: None known.

#### **SECTION IV – FIRST AID INSTRUCTIONS**

Skin Contact: Remove contaminated clothing. Wash affected area with soap and rinse with plenty of water. Get medical attention if irritation persists. Wash clothing before reuse.

Eye Contact: Flush with water for at least 15 minutes holding eyelid open. Get medical attention if symptoms persist.

Respiratory / Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion: Do not induce vomiting. Get medical attention immediately.

#### **SECTION V – FIRE FIGHTING INSTRUCTIONS**

Flash Point:	105°F (TCC)
Unusual Fire and Explosion Hazards:	Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapors can travel to a source of ignition and flash back.
Flammable Limits:	LEL:0.7, UEL: 6
Extinguishing Media:	Carbon Dioxide, Foam, Dry Chemicals, Water fog
Fire Fighting Procedures:	Air mask, goggles, and procedures for fighting chemical fires

#### **SECTION VI -ACCIDENTAL RELEASE MEASURES**

Special Precautions:	Avoid breathing vapors. Ventilate area. Remove all sources of ignition.
----------------------	---

Clean up methods:	Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.
-------------------	--

#### **SECTION VII - HANDLING AND STORAGE**

Handling:	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift.
-----------	--

Storage:	Store in a cool location (60-90°F) in a well ventilated area away from sources of heat. Do not puncture or incinerate (burn) cans. Do not stick pin, nail or any other sharp object into opening on top of can. Do not spray in eyes.
----------	---

Personal Protection:	None under normal use, avoid breathing vapors. In restricted Areas, use approved chemical / mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PIL / TLV limits.
----------------------	---

#### **SECTION VIII – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

Respiratory Protection:	A NIOSH / MSHA approved air purifying respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.
-------------------------	---

Page 2 of 3

Product: POA-12

Skin Protection:	None necessary under normal use. Solvent resistant required for prolonged or repeated contact.
------------------	--

Eye Protection:	None under normal use, however, use of safety glasses with splash guards or full face shield is recommended.
-----------------	--

Eye Washes: Eye wash stations should be located within 100 feet or 10 second walk of the work area.

### **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

Physical state:	Aerosol
Odor:	Aerosol
Boiling Range:	310°F – 500°F
Specific Gravity:	0.83
Vapor Density (Air = 1):	Heavier than air
pH:	N/A
Melting Point:	N/A
Evaporation Rate:	Slower than ether
Solubility in Water:	Complete

### **SECTION X – STABILITY AND REACTIVITY**

Stability:	Stable under normal storage conditions
Hazardous Polymerization:	Will not occur.
Hazardous decomposition byproducts:	May produce fumes when heated to decomposition. Fumes may contain carbon monoxide.
Incompatibility:	Strong oxidizing agents.

### **SECTION XI – TOXICOLOGICAL INFORMATION**

Carcinogenicity:			
	NTP Carcinogen: No	IARC Monographs: No	OSHA Regulated: No

### **SECTION XII – ECOLOGICAL INFORMATION**

No Information

### **SECTION XIII – DISPOSAL CONSIDERATIONS**

Recommended method of disposal:	Dispose of according to Federal, State and local regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.
---------------------------------	--

### **SECTION XIV – SHIPPING AND TRANSPORTATION INFORMATION**

U.S. Department of Transportation Ground (49 CFR)	
Proper Shipping Name:	Aerosol / Consumer Commodity
Hazard Class or Division:	Flammable Gas/ ORM-D
Identification Number:	UN 1950

### **SECTION XV – REGULATORY INFORMATION**

See Section II

### **SECTION XVI – OTHER INFORMATION**

Revision date: 03-09-07

DISCLAIMER: The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.