

PRODUCT INFORMATION:

SAF-T-EZE Dry-Moly Aerosol is an air-drying, greaseless, dry film lubricant and performs as a pre-applied anti-seize. A combination of molybdenum disulfide powder, and other solid lubricants in a high temperature binder makes **Dry-Moly Aerosol** is an ideal lubricant and anti-seize for a variety of applications from -100°F to 2400°F

GENERAL DISCRIPTION:

SAF-T-EZE Dry-Moly Aerosol is recommended for general plant maintenance and specifically for environments where clean, dry lubricant is required. The product lubricates and protects metal parts from wear and corrosion. The greaseless finish repels dirt and dust, and does not rub off, thus making it an ideal lubricant for dirty, dusty environments, where dirt can clog and interfere with grease based lubrication. **SAF-T-EZE Dry-Moly Aerosol** is resistant to water and water-based solutions. Exposure to temperatures above 300°F will add resistance to solvents. In maintenance applications, it is an excellent choice for lubricating dry bearings, or as an "easy-off" coating to repel dirt build-up in exhaust systems. The dry finish makes it excellent for applications where repeated handling of the lubricated parts is common.

PHYSICAL PROPERTIES:

| | |
|--------------------------------|---------------------|
| Color | Dark Grey |
| Temperature Range | -100°F to 2400°F |
| Specific Gravity | 0.7 |
| Propellant | Hydrocarbon |
| Flash Point C.O.C. | 15°F |
| Particle Size | < 34 microns |
| Coefficient of Friction | K value 0.13 |

APPLICATION:

Shake can well. Make sure that the area to be sprayed is clean and dry. Spray the area to be lubricated at a distance of 8-12 inches. Allow 5-10 minutes to dry before handling parts.

Note: This product is not recommended for pure oxygen systems.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.

TECHNICAL SUPPORT

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

PART NUMBERS

85856 8.25 oz DMA

TURNKEY SOLUTIONS

As an ISO 9001:2015 certified company, SAF-T-LOK can design or refine products to fit your company's specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:
www.saftlok.com