

SAF-T-EZE[®]

TDS-EP

E.P. Lubricant

Technical Data Sheet

GENERAL INFORMATION: *SAF-T-EZE Extreme Pressure Bearing Lubricant* is a multi-purpose high performance lithium soap thickened grease that exhibits superior high temperature stability to as high as 300°F for intermittent use. This grease has been compounded for high as well as low speed bearings and provides higher service performance than conventional greases. *SAF-T-EZE E.P. Lubricant* includes additives to resist extreme pressures and contains corrosion inhibitors to prevent rust promotion.

PHYSICAL PROPERTIES:

Color	Amber
NLGI	2
Drop Point	380°F
Thickener Type	Lithium Hydrostearate
Base Oil Properties:	
Viscosity @ 100°F	900
Viscosity @ 100°C	80
Penetration @ 77 °F:	
Worked	285
Wheel Bearing Test	Pass
Water Washout	Nil
Rust Protection	Pass
Texture	Smooth

NOTE: This product is not recommended for pure oxygen systems.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. *SAF-T-EZE Div., STL Compound Corporation* is not responsible for loss, claim or damages resulting from use of its products.