

Gasket Sealant #2

Technical Data Sheet

GENERAL INFORMATION:

SAF-T-EZE Gasket Sealant #2 is a thick, dark paste. This product emits an alcohol odor. Gasket Sealant # 2 sets to a semi-flexible gasket upon alcohol evaporation. Gasket Sealant # 2 reliably seals gaskets, flanges, connections, and other flexible assemblies. It resists gasoline, motor oil, diesel fuel, transmission fluid, antifreeze, and water. This product performs to 400°F.

PRODUCT CHARACTERISTICS:

COLOR	Black paste
SPECIFIC GRAVITY	1.25
VISCOSITY	250,000 cps
FLASH POINT	54° F
TEMPERATURE RANGE	-65°F TO 400°F
STORAGE STABILITY	+12 MONTHS @ <75°F
SEALING CAPACITY	5000 psi

Gasket Sealant # 2 is not to be utilized in pure oxygen or oxygen rich systems. It is also not to be used for chlorine or other similarly aggressive oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

NOTE: May affect certain plastics and paints. Try in remote area before using.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.