

## Non-Metallic White Anti-Seize

## Technical Data Sheet

---

**GENERAL INFORMATION: SAF-T-EZE Non-Metallic White Anti-Seize** is metal free and recommended where copper must be avoided. It is an excellent anti-seize for titanium, stainless steel and other alloy steels. It prevents corrosion, galling, and seizure between metal parts, and is recommended for service up to 2400°F.

**PRODUCT DESCRIPTION: SAF-T-EZE Non-Metallic White Anti-Seize** has been specifically formulated to meet the requirements of extreme high temperature applications. It is manufactured with the highest quality grease and solid lubricants. Non-Metallic White Anti-Seize does not contain copper, nickel or any metallic ingredients.

### PHYSICAL PROPERTIES:

Color:	White
Temperature Range:	-65°F to 2400°F
NLGI:	1
Specific Gravity:	1.19
Weight per Gallon:	9.9 lbs.
Penetration:	150 - 250

**APPLICATION: SAF-T-EZE Non-Metallic White Anti-Seize** is particularly recommended for applications where different metals are being used. Its non-metallic make up provides a lubricating barrier that prevents galvanic corrosion, even at extreme temperatures. It is an excellent choice to lubricate parts made of the various stainless steel grades. It is also a prime choice where nickel alloys, titanium, or other hard metals are in use. Use on threaded parts, bushings, gears, valve stems, chains, sprockets, levers, hinges, pivots, rollers, heat exchanger bolts, manifolds, or in any threaded joint where a high performance metal free anti-seize is required.

Note: This product is not recommended for pure oxygen systems.

---

**IMPORTANT NOTICE:** All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.