

# SAF-T-EZE<sup>®</sup>

TDS-PST

## Pipe-Seal w/ Teflon<sup>®</sup>

Technical Data Sheet

**GENERAL INFORMATION:** *SAF-T-EZE Pipe-Seal* and Anti-Seize compound with Teflon\* is used where resistance to chemicals is needed. It can be used on services that contain gasoline, kerosene, LP gases, oil, refrigerants/solvents, caustics, many acids, water, gas and steam.

It can be used on pipes and threaded connections of all materials: iron, stainless steel, aluminum, brass, plastic, etc. *SAF-T-EZE Pipe-Seal* is recommended for heavy duty sealing on joints larger than 3/4 inch in diameter. This paste will not run, drip, or separate and is self-lubricating in assembly.

*SAF-T-EZE Pipe-Seal* can be applied as low as 10°F. It is non-staining and withstands pressures to 10,000 psi.

### PHYSICAL PROPERTIES:

Color	White
Specific Gravity	1.3
Performance Temperature	-100°F to +500°F
Flash Point: C.O.C.	350°F

**SHELF LIFE:** There is no change in consistency or appearance after one year in a closed container.

**CLEAN UP:** Any petroleum derived solvent, such as paint thinner, naphtha, or petroleum distillate. Safety Solvent is also recommended for removal from fabric.

\* Teflon is a registered trademark of DuPont

NOTE: This product is not recommended for pure oxygen systems.

---

**IMPORTANT NOTICE:** All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. *SAF-T-EZE Div., STL Compound Corporation* is not responsible for loss, claim or damages resulting from use of its products.