

Safety Data Sheet Marine Grade Anti-Seize

SDS Revision Date:

07/04/18

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Identity	SAF-T-EZE MARINE GRADE ANTI-SEIZE
Alternate Names	Part Numbers: 83437, 83457, 83478 Product Type: Lubricating Grease
1.2. Relevant identified uses of the substance or mixtu	re and uses advised against
Intended use	Lubricating Grease
Application Method	See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	SAF-T-LOK International Corporation 300 EISENHOWER LANE NORTH
	LOMBARD, IL 60148
Emergency	
CHEMTREC (USA)	(800) 424-9300
24 hour Emergency Telephone No.	(703) 527-3887
Customer Service: SAF-T-LOK International Corporation	(630) 495-2001

2. Hazard identification of the product

2.1. Classification of the substance or mixture

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

[Prevention]:

P273 Avoid release to the environment. [Response]:

P391 Collect spillage.



SDS Revision Date:

07/04/2018

[Storage]: No GHS storage statements

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum distillates, hydrotreated heavy paraffinic CAS Number: 0064742-54-7	60-80	Acute Tox. 4;H312	[1]
Graphite CAS Number: 0007782-42-5	15-30		[1][2]
Copper CAS Number: 0007440-50-8	10-25		[1][2]
Aluminum CAS Number: 00007429-90-5	1.0-10		[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance. *The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
4.2. Most important syn	nptoms and effects, both acute and delayed
Overview	Skin Contact: Usually no effect, however, as with any chemical, prolonged, excessive, or repeated exposure may cause mild to moderate skin irritation, exhibited by redness, drying and cracking of unprotected skin.
	Eye Contact: May irritate with slight pain and redness.



SDS Revision Date:

07/04/2018

Respiratory/ Inhalation: Usually none, however, as with any chemical product, some irritation may occur.

Ingestion: Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury.

Medical conditions generally aggravated by exposure: None known, however any chemical product may enhance allergies already present in certain individuals. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon and sulfur

5.3. Advice for fire-fighters

Air mask and procedures for fighting chemical fires. Do not inhale gases.

Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

ERG Guide No.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent material from entering floor drains, sewers, or any bodies of water. Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

7. Handling and storage

7.1. Precautions for safe handling

No special precautions necessary if used properly. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities



SDS Revision Date:

07/04/2018

Handle containers carefully to prevent damage and spillage.

Isolated storage facility/ warehouse not required. Store in a cool, dry location (60-90°F) in a well-ventilated area in original container. Keep container tightly closed when not in use.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

None

8. Exposure controls and personal protection

8.1. Control parameters

Exposure				
CAS No.	Ingredient	Source	Value	
		OSHA	TWA 15 mg/m3TWA 15 mppcf	
0007782-42-5	Graphite	ACGIH	TWA: 2 mg/m3	
0001102 42 0		NIOSH	TWA 2.5 mg/m3 (resp)	
		Supplier	No Established Limit	
		OSHA	No Established Limit	
0064742-54-7	Petroleum distillates, hydrotreated heavy	ACGIH	No Established Limit	
paraffinic		NIOSH	No Established Limit	
		Supplier	No Established Limit	
		OSHA	TWA: 15 mg/m3 (total) TWA: 5 mg/m3 (resp)	
		ACGIH	TWA: 1.0 mg/m3 Revised 2008	
0007429-90-5	Aluminum	NIOSH	TWA: 10 mg/m3 (total) TWA: 5 mg/m3 (resp)	
		Supplier	No Established Limit	
0007440-50-8 Copper	Copper	OSHA	TWA: 1 mg/m3 [*note: The PEL also applies to other copper compounds (as cu) except copper fume.]	
		ACGIH	TWA: 0.2 mg/m3 (fume) 1 mg/m3 (dusts and mists)	
		NIOSH	TWA: 1 mg/m3 [*note: The REL also applies to other copper compounds (as cu) except copper fume.]	
		Supplier	No Established Limit	

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

Ũ				
CAS No.	Ingredient	Source	Value	
	82-42-5 Graphite C		Select Carcinogen: No	
0007782-42-5			Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
			Select Carcinogen: No	
0064742-54-7 Petroleum distillates, hydrotreated	NTP	Known: No; Suspected: No		

Carcinogen Data



SDS Revision Date:

07/04/2018

	heavy paraffinic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007429-90-5 Aluminum		OSHA	Select carcinogen: No
	Aluminum	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007440-50-8 Copper		OSHA	Select carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls	
Respiratory	No respiratory protection required, but normal good ventilation is recommended. Forced ventilation may be required if concentrations exceed normal use exposure.
Eyes	Not required if application method is proper. Avoid contact with eyes.
Skin	Wear overalls to keep skin contact to a minimum. Use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Silver Paste
Odor	Mild/Inoffensive
Odor threshold	Not Measured
рН	Not determined
Melting point / freezing point	Not determined
Initial boiling point and boiling range	N/A
Flash Point	350 F° (C.0.C.)
Evaporation rate (Ether = 1)	Not determined
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A
	Upper Explosive Limit: N/A
Vapor pressure (Pa)	N/A
Vapor Density	N/A
Specific Gravity	1.2
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured



SDS Revision Date:

07/04/2018

Auto-ignition temperature Decomposition temperature Viscosity (cSt) VOC % % Solid 9.2. Other information Not Measured Not Measured <0.1% (Organic solvents) % (cut) 35-48%

9.2. Other information DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Page 6 of 11



SDS Revision Date:

07/04/2018

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Incompatible with strong oxidizing agents

10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

10.6. Hazardous decomposition products

Oxides of carbon and sulfur

11. Toxicological information

Acute toxicity

Copper dust and mists: Can cause irritation of eyes, mucous membranes, skin and respiratory tract. Chronic overexposures: Can cause reduction in the number of red blood cells (anemia), skin abnormalities (pigmentation changes) and hair discoloration.

Copper fume: Can cause irritation of eyes, mucous membranes and respiratory tract.

Acute overexposures:Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever). Wilson's disease may be affected by copper exposure.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Petroleum distillates, hydrotreated heavy paraffinic - (64742-54-7)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Graphite - (7782-42-5)	No data	No data	No data	No data	No data
	available	available	available	available	available
Copper - (7440-50-8)	2,500.00, Rat -	>2,000.00, Rat -	No data	5.11, Rat -	No data
	Category: 5	Category: 5	available	Category: NA	available
Aluminum (AI) - (7429-90-5)	No data	No data	No data	No data	No data
	available	available	available	available	available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



SDS Revision Date:

07/04/2018

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Petroleum distillates, hydrotreated heavy paraffinic - (64742-54-7)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Graphite - (7782-42-5)	Not Available	Not Available	Not Available
Copper - (7440-50-8)	0.0103, Pimephalespromelas	0.0025, Daphnia magna	0.018 (72 hr), Pseudokirchneriell a subcapitata
Aluminum (Al) - (7429-90- 5)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment



SDS Revision Date:

07/04/2018

This product contains no PBT/vPvB chemicals. **12.6. Other adverse effects** No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA		
14.1. UN number	Not Applicable	Not Regulated	Not Regulated		
14.2. UN proper shipping name	Not Regulated	Environmentally hazardous substance, liquid, N.O.S	Not Regulated		
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label:	IMDG: 9 Sub Class: Not Applicable	Air Class: Not Applicable		
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable		
14.5. Environmental hazards					
IMDG	MDG Marine Pollutant: Not Applicable				
14.6. Special precautions for user					
١	No further information				

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	Not Regulated
US EPA Tier II Hazards	Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Copper (5,000.00)

EPCRA 302 Extremely Hazardous : (No Product Ingredients Listed)



SDS Revision Date:

07/04/2018

EPCRA 313 Toxic Chemicals:

Aluminum (AI)

Copper

Proposition 65 - Carcinogens (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%): (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%): (No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Aluminum (AI)

Copper

Graphite

Penn RTK Substances (>1%):

Aluminum (AI)

Copper

Graphite



SDS Revision Date:

07/04/2018

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H312 Harmful in contact with skin.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document