

Safety Data Sheet TGEL LUBE



SDS Revision Date:

01/07/18

International Corporation

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity TGEL LUBE
Alternate Names Part Numbers: 85956
Product Type: Lubricating Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Lubricating Grease
Application Method Aerosol

1.3. Details of the supplier of the safety data sheet

Company Name SAF-T-LOK International Corporation
300 EISENHOWER LANE NORTH
LOMBARD, IL 60148

Emergency

CHEMTREC (USA) (800) 262-8200 ID 1195
24 hour Emergency Telephone No. (703) 527-3887
Customer Service: SAF-T-LOK International Corporation (630) 495-2001

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Gases under pressure	Compressed gas
Category 2	Skin corrosion/ irritation
Category 2	Specific target organ toxicity (repeated exposure)
Category 3	Specific target organ toxicity (single exposure)
Category 1	Aspiration Toxicity
Category 1	Flammable aerosols
Category 2A	Serious eye damage/ eye irritation
Category 2	Reproductive toxicity

2.2. Label elements

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation



Hazard Statements

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

Causes damage to organs (respiratory system), through repeated exposure

May be fatal if swallowed or enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Appearance: Opaque

Physical State: Aerosol

Odor: Solvent

[Prevention]:

Obtain special instructions before use

Wash hands thoroughly after handling

Wear protective gloves, clothing, and eye and face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should be allowed out of work place

Do not eat drink or smoke while using this product

Use only outdoors or in well-ventilated area

Keep away from heat/spark/open flames/hot surfaces — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

[Response]:

IF ON SKIN: Wash with plenty of soap and water

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

[Storage]:

Store locked up

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperature exceeding 50°C / 122°F

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Chemical Name	CAS-No	Weight %
PROPANE/ ISOBUTANE/ N-BUTANE	68476-86-8	20-30
HEXANE	110-54-3	20-30
ACETONE	67-64-1	30-40

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. First aid measures

4.1. Description of first aid measures

General

Avoid contact with skin, eyes, and clothing. Avoid breathing, vapors, mist, or gas.
In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser. If irritation persists contact a physician

Ingestion

If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Irritating to skin and eyes. Inhalation causing Central Nervous System effects. Ingestion causing lung damage.

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; Water fog, dry chemical, CO₂, cool containers/ tanks with water
DO NOT use a solid water stream it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Flammable or extremely flammable aerosol. Container may burst in fire.

5.3. Advice for fire-fighters

Air mask and procedures for fighting chemical fires. Do not inhale gases.

Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use with adequate ventilation to keep the exposure level below the OELS

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Report spills as required by local and federal regulations

6.3. Methods and material for containment and cleaning up

Prevent material from entering floor drains, sewers, or any bodies of water.

Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

7. Handling and storage

7.1. Precautions for safe handling

No special precautions necessary if used properly. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift. AVOID CONTACT WITH EYES. Do not stick pin or sharp object into opening on top of can. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Isolated storage facility/ warehouse not required. Store in a cool, dry location (60-90°F) in a well-ventilated area in original container. Keep container tightly closed when not in use.

Incompatible materials: Strong Oxidizing Agents, AND Strong Acids.

Aerosol level: 3

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

7.3. Specific end use(s)

None

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA 250 ppm TWA: 590 mg/m ³
HEXANE 110-54-3	TWA: 50 ppm Skin-potential significant Contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m ³ (vacted) TWA: 50 ppm (vacted) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F. 2d 962 (11th Cir., 1992).

8.2. Exposure controls

Respiratory

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Eyes

Safety glasses with side-shields.

Skin

Chemical resistant apron. Protective gloves.

Engineering Controls

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

Other Work Practices Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. Vacated limits revoked by the court appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Clear
Odor	Solvent
Odor threshold	Not Measured
pH	Not determined
Melting point / freezing point	Not determined
Initial boiling point and boiling range	Not determined
Flash Point	-96.4 °C / -141°F
Evaporation rate (Ether = 1)	Not determined
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A Upper Explosive Limit: N/A
Vapor pressure (Pa)	N/A
Vapor Density	N/A
Specific Gravity	0.730
Solubility in Water	Practically Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	48.43

Safety Data Sheet

TGEL LUBE

SDS Revision Date:

01/07/2018

SAF-T-LOK

International Corporation

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

None under normal processing

10.4. Conditions to avoid

Extremes of temperature and direct sunlight

10.5. Incompatible materials

Strong oxidizing agents and acids

10.6. Hazardous decomposition products

Oxides of carbon

11. Toxicological information

Acute toxicity

Product Information: Product does not present an acute toxicity hazard based on known information

Inhalation: Exposure to high vapor concentrations may cause nervous systems effects such as headache, nausea, and dizziness.

Eye Contact: May cause irritation

Skin Contact: Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion: Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal

Ingredient	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone 67-64-1	=5800 mg/kg	20,000 mg/kg (Rabbit)	= 50,100 mg/m ³ (rat) 8 h
Hexane 110-54-3	-	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

12. Ecological information

Aquatic Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to fish	Toxicity to Algae	Toxicity to daphnia and other aquatic invertebrates
Acetone 67-64-1	4.74 -6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 – 8120 mg/L/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	--	10294 – 17704 mg/L EC50 Daphnia magna 48h Static 12600 – 12700 mg/L EC50 Daphnia Magna 48h
Propane/Isobutane/N-butane 68476-86-8	--	--	--
Hexane 110-54-3	2.1 – 2.98 mg/L LC50 Pimephales promelas 96h flow-through	--	--

Chemical Name	Log Pow
Propane/isobutene/N-butane 68476-86-8	2.8
Acetone 67-64-1	-0.24

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance. Do not re-use empty containers.

14. Transport information

DOT Ground

Consumer commodity ORM-D or Limited quantity

IATA

UN1950, aerosols, flammable, 2.1, LTD. QTY

IMDG

UN1950, aerosols, 2.1, LTD. QTY

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

15. Regulatory information

Chemical name	TSCA	DSL/NDSL	EINEC/ELINCS	ENCS	IECS	KECL	PICCS	AICS
Propane/isobutene/N-butane	X	X	X	Not listed	X	X	X	X
Acetone	X	X	X	X	X	X	X	X
Hexane	X	X	X	X	X	X	X	X

SARA 313

Section 313 is Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemical or chemicals, which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313- Threshold Values %
Hexane	110-54-3	20-30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product contains substances, which are regulated pollutants pursuant to the Clean Water Act (40 cfr 122.21 and 40 CFR 122.42): This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the comprehensive Environmental Response Compensation and Liability Act. This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act or the Superfund Amendments and Reauthorization Act. There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substance RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb	--	RQ 5000 lb final RQ RQ 2270 kg final RQ
HEXANE 110-54-3	5000 lb	--	RQ 5000 lb final RQ RQ 2270 KG final RQ

Safety Data Sheet

TGEL LUBE

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

16. Other information

NFPA Health Hazard: 2 Flammability: 4 Instability: 0 Physical and chemical hazards: -

HMS Health Hazard: 2 Flammability: 4 Physical Hazard: 1 Personal Protection: B

The full text of the phrases appearing in section 3 is:

H312 Harmful in contact with skin.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document