

GENERAL INFORMATION:

SAF-T-EZE BELT-DRESS was formulated to meet industrial demands for increased operating efficiency and longer belt life. The application of **SAF-T-EZE BELT-DRESS** synthetic polymer reduces stiffness and restores life to worn and checked belts. These polymers also provide water resistance. Increases efficiency is increased by reduces belt slippage due to tackifiers in the formulating that improve traction between belts and pulleys and at the same time reduce belt tension.

PHYSICAL PROPERTIES:

| | |
|------------------|-----------|
| Flash Point | -42°F |
| Specific Gravity | 0.98gm/cc |

APPLICATIONS:

- Improves belt traction
- Reduces belt tension
- Stops belt squeal
- Eliminated power loss
- Provides water resistance
- Extends belt life
- Extends pulley bearing life

DIRECTIONS: Stop belt and allow too cool to room temperature. Spray inner belt and pulley surface. Apply a small amount at a time, do not flood surface. Reapply at regular intervals to maintain full power.

USE ON: Flat, round and V-belts of all sizes.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.

TECHNICAL SUPPORT

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-site support when necessary within 24 hours.

PART NUMBERS

85656 9oz

TURNKEY SOLUTIONS

As an ISO 9001:2008 certified company, SAF-T-LOK can design or refine products to fit your companies specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:
www.saftlok.com