

TECHNICAL SUPPORT

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

PART NUMBERS

85456 14oz

SPECIFICATIONS

MIL-PRF-907E

TURNKEY SOLUTIONS

As an ISO 9001:2015 certified company, SAF-T-LOK can design or refine products to fit your company's specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:

www.saftlok.com**PRODUCT DESCRIPTION:**

SAF-T-EZE GASKET-OFF is a solvent based aerosol designed to remove baked-on gaskets, gasket cement, carbon deposits, dried oils, grease, and most paints.

SAF-T-EZE GASKET-OFF is safe to use on metals but it is not recommended for plastic surfaces, linoleum, fiberglass, or synthetic fabrics.

GENERAL INFORMATION:

SAF-T-EZE GASKET-OFF is a methylene chloride based, stripper designed to remove baked-on gaskets and residue from metal surfaces. It is aerosol based and will removed stuck-on gaskets, residues and most paints.

PHYSICAL PROPERTIES:

Color	None/Clear
Odor	Solvent
V.O.C.	31.59%
Flash Point	-96.4°C / -141°F
Temperature Range	-30°F to 550°F
Specific Gravity	1.063 gm/cc

APPLICATION:

Shake can well before using. Spray area to be removed and allow product to work for ten minutes. Remove old gasket with a scraper or putty knife. For thicker gaskets, repeat if necessary.

*NOTE: This product is not recommended for use on pure oxygen systems.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.