

PRODUCT DESCRIPTION:

SAF-T-EZE Non-Metallic White Anti-Seize has been specifically formulated to meet the performance requirements of the industry. It is manufactured with high-purity grease and solid lubricants. **SAF-T-EZE Non-Metallic White Anti-Seize** provides ultimate anti-seize protection in industrial applications where the environment or regulations dictate a non-metallic product.

GENERAL INFORMATION:

SAF-T-EZE Non-Metallic White Anti-Seize is a metal free anti-seize that is designed to be used in applications where metal containing products are not allowed. It is an excellent anti-seize for titanium, stainless steel, and other alloy steels. It prevents corrosion, galling, and seizure between metal parts, and is recommended for service to 2000°F.

PHYSICAL PROPERTIES:

Color	White
Temperature Range	-60°F to 2000°F
NLGI	3
Specific Gravity	1.2
Weight per Gallon	10.0 lb
Penetration Range	200-250
Drop Point	350°F
Flash Point C.O.C.	350°F
Particle Size	34 microns
Coefficient of Friction	K value 0.17

APPLICATION:

SAF-T-EZE Non-Metallic White Anti-Seize is particularly recommended where different metals are being used. Its non-metallic make up provides a lubricating barrier that prevents galvanic corrosion, even at extreme temperatures. Use on threaded parts, bushings, gears, valve stems, chains, sprockets, levers, hinges, pivots, rollers, heat exchanger bolts, manifolds, or in any threaded joint where a high purity anti-seize is required.

NOTE: This product is not recommended for pure oxygen systems.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its

TECHNICAL SUPPORT

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

PART NUMBERS

83837	8oz	NMWBT-8
83857	16oz	NMWBT-16
83861	1kg	NMW-1k

SPECIFICATIONS

MIL-PRF-907E

TURNKEY SOLUTIONS

As an ISO 9001:2008 certified company, SAF-T-LOK can design or refine products to fit your companies specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:
www.saftlok.com