

**TECHNICAL SUPPORT**

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

**PART NUMBERS**

85956 10oz

**SPECIFICATIONS**

MIL-PRF-907E

**TURNKEY SOLUTIONS**

As an ISO 9001:2008 certified company, SAF-T-LOK can design or refine products to fit your companies specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:

www.saftlok.com

**PRODUCT DESCRIPTION:**

**SAF-T-EZE T-GEL LUBE** features high adhesive strength, quickly evaporating solvents, and it continues lubrication over a wide temperature range. **SAF-T-EZE T-GEL LUBE** adheres to surfaces, and resists throw-off squeeze out when subjected to high pressures, vibrations, or repeated impact. It allows maximum penetration and rapid set up of grease-like lubricant. **SAF-T-EZE T-GEL LUBE** will withstand high temperatures without melting, it also has a high drop point and helps prevent rust and corrosion.

**GENERAL INFORMATION:**

**SAF-T-EZE T-GEL LUBE** is a transparent, high-pressure lubricant with high surface adhesion. A unique combination of natural and synthetic lubrication agents coupled with a high molecular weight polymer (Polytetrafluoroethylene or PTFE) makes this product one of the best lubricants available.

**PHYSICAL PROPERTIES:**

<b>Color</b>	<b>None/Clear</b>
Odor	Solvent
<b>V.O.C.</b>	<b>48.43%</b>
Flash Point	-96.4°C / -141°F
<b>Temperature Range</b>	<b>-30°F to 550°F</b>
Specific Gravity	0.73 gm/cc

**APPLICATION:**

Shake can well before using. Saturate area to be lubricated and allow solvent to evaporate. Use an extension tube for hard to reach places. **SAF-T-EZE T-Gel Lube** may be used on but not limited to; door hinges, open gears, wire ropes and cables, chains and sprockets, conveyors, manifold heat valves, and above water line marine applications.

**IMPORTANT NOTICE:** All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its