

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

1. Identification

1.1. Product identifier

Product Identity

Hydraulic Sealant Product Type: Anaerobic Adhesive/ Sealant

Alternate Names

Product Number: 26921, 26931, 26941, 26943

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

Anaerobic Adhesive/ Sealant.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

SAF-T-LOK International Corporation
300 EISENHOWER LANE NORTH
LOMBARD, IL 60148

Emergency

CHEMTREC (USA)

(800) 424-9300

24 hour Emergency Telephone No.

(703) 527-3887

Customer Service: SAF-T-LOK International Corporation

(630) 495-2001

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Acute Tox. 4;H332

Harmful if inhaled.

Skin Irrit. 2;H315

Causes skin irritation.

Eye Irrit. 2;H319

Causes serious eye irritation.

STOT RE 2;H373

May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)

Aquatic Chronic 3;H412

Harmful to aquatic life with long lasting effects.

2.2. Label elements



Warning

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

[Prevention]:

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

[Storage]:

No GHS storage statements

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Triethylene glycol dimethacrylate CAS Number: 0000109-16-0	75 - 100	Not Classified	[1]
Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-Ethane-1,2-diol, ethoxylated CAS Number: 0025322-68-3	25 - 50	Not Classified	[1]
Benzisothiazol-3(2H)-one, 1,1-dioxide CAS Number: 0000081-07-2	1 - 5	Not Classified	[1]
Amorphous fumed silica	1 - 5	Combustible Dust	[1]

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

CAS Number: 0112945-52-5		Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335	
Cumene hydroperoxide CAS Number: 0000080-15-9	1 - 5	Org. Perox. E;H242 Acute Tox. 3;H331 Acute Tox. 4;H312 Acute Tox. 4;H302 STOT RE 2;H373 Skin Corr. 1B;H314 Aquatic Chronic 2;H411	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Relative routes of entry: Skin, Inhalation, Eyes. Ingestion Skin Contact: Usually no effect, however, as with any chemical, prolonged, excessive, or repeated exposure may cause mild to moderate skin irritation, exhibited by redness, drying and cracking of unprotected skin. Eye Contact: May irritate with slight pain and redness. Respiratory/ Inhalation: Usually none, however, as with any chemical product, some irritation may occur. Ingestion: Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury. Treat symptomatically. See section 2 for further details.
Inhalation	Harmful if inhaled.
Eyes	Causes serious eye irritation.
Skin	Causes skin irritation.

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

Section 5. Fire-fighting measures

5.1. Extinguishing media

Carbon Dioxide, Foam, Dry Chemicals.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon, Oxides of nitrogen.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Possible exothermic reaction leading to substrate ignition and fume generation.

Air mask and procedures for fighting chemical fires. Do not inhale gases.

ERG Guide No. ---

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid contact with eyes, skin, and clothing. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool location (60-90°F) in a well ventilated area away from sources of heat. Keep container tightly closed when not in use.

Incompatible materials: Reducing agents. Strong Oxidizers

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift. Wear personal protective equipment as outlined in Section 8 of this SDS.

Section 8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000080-15-9	Cumene hydroperoxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000081-07-2	Benzisothiazol-3(2H)-one, 1,1-dioxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000109-16-0	Triethylene glycol dimethacrylate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0025322-68-3	Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0112945-52-5	Amorphous fumed silica	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Skin

Wear overalls to keep skin contact to a minimum. Not required, but if desired, use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Brown Liquid
Odor	Mild
Odor threshold	Not determined
pH	N/A
Melting point / freezing point	N/A
Initial boiling point and boiling range	> 300 °F
Flash Point	205°F (T.C.C.)
Evaporation rate (Ether = 1)	N/A
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A Upper Explosive Limit: N/A
Vapor pressure (Pa)	(mm Hg.): < 5 @ 30 °F
Vapor Density	(Air = 1): N/A
Specific Gravity	1.07
Solubility in Water	Partial
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	< 0.1 %

9.2. Other information

No other relevant information.

Section 10. Stability and reactivity

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Reducing agents. Strong Oxidizers

10.6. Hazardous decomposition products

Oxides of carbon, Oxides of nitrogen.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Triethylene glycol dimethacrylate - (109-16-0)	10,837.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available	No data available	No data available
Poly(oxy-1,2-ethanediyl),α-hydro-ω-hydroxy-Ethane-1,2-diol, ethoxylated - (25322-68-3)	30,200.00, Rat - Category: NA	20,001.00, Rabbit - Category: NA	No data available	No data available	No data available
Benzisothiazol-3(2H)-one, 1,1-dioxide - (81-07-2)	No data available	No data available	No data available	No data available	No data available
Amorphous fumed silica - (112945-52-5)	3,160.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Cumene hydroperoxide - (80-15-9)	382.00, Rat - Category: 4	1,520.00, Rabbit - Category: 4	No data available	No data available	220.00, Rat - Category: 2

Carcinogen Data

CAS No.	Ingredient	Source	Value

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

0000080-15-9	Cumene hydroperoxide	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000081-07-2	Benzisothiazol-3(2H)-one, 1,1-dioxide	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000109-16-0	Triethylene glycol dimethacrylate	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025322-68-3	Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112945-52-5	Amorphous fumed silica	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

Section 12. Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Triethylene glycol dimethacrylate - (109-16-0)	17.20, Fish	Not Available	101.00 (72 hr), Algae
Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated - (25322-68-3)	101.00, Poecilia reticulata	357.142, Daphnia magna	398.913 (72 hr), Pseudokirchneriella subcapitata
Benzisothiazol-3(2H)-one, 1,1-dioxide - (81-07-2)	Not Available	Not Available	Not Available
Amorphous fumed silica - (112945-52-5)	Not Available	Not Available	Not Available
Cumene hydroperoxide - (80-15-9)	3.90, Oncorhynchus mykiss	18.40, Daphnia magna	3.10 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No;		
14.6. Special precautions for user	No further information		

Section 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS 1988 Classification	D2B
US EPA Tier II Hazards	Fire: No Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): Yes

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Benzisothiazol-3(2H)-one, 1,1-dioxide
Cumene hydroperoxide

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Safety Data Sheet

Hydraulic Sealant : Anaerobic Adhesive/ Sealant

SAF-T-LOK

SDS Revision Date:

01/07/2018

International Corporation

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date 10/10/2017

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document