

Safety Data Sheet

RTV PRESSURIZED SILICONE RED



SDS Revision Date:

01/15/2019

International Corporation

1. Identification

1.1. Product identifier

Product Identity RTV Pressurized Silicone

Alternate Names 73648

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Silicone Sealant.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name SAF-T-LOK International Corporation
300 EISENHOWER LANE NORTH
LOMBARD, IL 60148

Emergency

CHEMTREC (USA) (800) 424-9300

24 hour Emergency Telephone No. (703) 527-3887

Customer Service: SAF-T-LOK International Corporation (630) 495-2001

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Repr. 2;H361F Suspected of damaging fertility.
Gases Under Pressure: Compressed Gas

2.2. Label elements



Warning

H361f Suspected of damaging fertility.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

P260 Do not breathe dust / fume/ mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P281 Use personal protective equipment as required.

Contains gas under pressure; May explode if heated

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P308+313 IF exposed or concerned: Get medical advice / attention.

P331 Do NOT induce vomiting.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated middle CAS Number: 0064742-46-7	1 - 5	Asp. Tox. 1;H304 Skin Irrit. 2;H315	[1]
Methyltriacetoxysilane CAS Number: 0004253-34-3	1 - 5	Acute Tox. 4;H302 Skin Corr. 1B;H314	[1]
Silanetriol, ethyl-, triacetate CAS Number: 0017689-77-9	1 - 5	Acute Tox. 4;H302 Skin Corr. 1B;H314	[1]
Cyclotetrasiloxane, octamethyl- CAS Number: 0000556-67-2	0.10 - 1.0	Repr. 2;H361f Aquatic Chronic 4;H413	[1]
1,1-Difluoroethane CAS Number: 75-37-6	<1%	Compressed Gas	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Remove contacts if present. Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	No specific symptom data available. Treat symptomatically. Suspected of damaging fertility.
-----------------	---

Section 5. Fire-fighting measures

5.1. Extinguishing media

Water fog, foam, carbon dioxide and dry chemical.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: This product reacts with water, moisture, or humid air to evolve following compounds. Acetic acid. Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon dioxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

5.3. Advice for fire-fighters

Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

By heating and fire, harmful vapors / gases may be formed. Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots and self-contained breathing apparatus. Move containers from fire area if you can do so without risk.

Do not breathe dust / fume/ mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

ERG Guide No. ---

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Eliminate sources of ignition.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth). Clean surface thoroughly to remove residual contamination.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Provide adequate ventilation. Use care in handling/storage. Obtain special instructions before use. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Pregnant and breastfeeding women must not handle this product. Do not breathe mist or vapor. Avoid contact with eyes. Avoid contact with skin. Avoid long term exposure.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Stored locked up. Keep container tightly closed. Keep out of reach of children. Store in a cool dry place out of direct sunlight. Keep in original container.

Incompatible materials: Strong oxidizing agents. Water and moisture.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 8. Exposure controls and personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0000556-67-2	Cyclotetrasiloxane, octamethyl-	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0004253-34-3	Methyltriacetoxysilane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0017689-77-9	Silanetriol, ethyl-, triacetate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0064742-46-7	Distillates (petroleum), hydrotreated middle	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
75-37-6	1,1-Difluoroethane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³ OSHA PEL and 10 mg/m³ ACGIH.

8.2. Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Wear tightly sealed safety glasses. An eye wash station is suggested as a good workplace practice.
- Skin** Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 9. Physical and chemical properties
--

9.1. Information on basic physical and chemical properties

Appearance	Red paste under pressure
Odor	Acetic acid
Odor threshold	Not determined
pH	Not Available
Melting point / freezing point	Not Available
Initial boiling point and boiling range	Not Available
Flash Point	141.8 °F (> 96 °C) Closed cup
Evaporation rate (Ether = 1)	< 1 (Butyl Acetate = 1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Available Upper Explosive Limit: Not Available
Vapor pressure (Pa)	(mm Hg.): Negligible (25°C)
Vapor Density	(Air = 1): >1
Specific Gravity	1.04
Solubility in Water	Not Soluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	30 grams per liter
Relative Density	1.04 (25 °C)

9.2. Other information

No other relevant information.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 10. Stability and reactivity

10.1. Reactivity

Not Normally Reactive

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

10.4. Conditions to avoid

Avoid excessive heat and flame

10.5. Incompatible materials

Strong oxidizing agents, Strong bases, and strong acids. Water and moisture.

10.6. Hazardous decomposition products

This product reacts with water, moisture, or humid air to evolve following compounds. Acetic acid. Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon dioxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm/4hr
Distillates (petroleum), hydrotreated middle - (64742-46-7)	> 5,000.00, Rat - Category: NA	---	---	---	---
Methyltriacetoxysilane - (4253-34-3)	1,600, Rat - Category: 4	---	---	---	---
Silanetriol, ethyl-, triacetate - (17689-77-9)	1,460.00, Rat - Category: 4	---	---	---	---
Cyclotetrasiloxane, octamethyl- - (556-67-2)	2,000.00, Rat - Category: 4	4,640.00, Rabbit - Category: 5	36.00, Rat - Category: NA	---	---
1,1-Difluoroethane – (75-37-6)	--	--	--	--	437,500 Rat Category 4

Safety Data Sheet

RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000556-67-2	Cyclotetrasiloxane, octamethyl-	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0004253-34-3	Methyltriacetoxysilane	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0017689-77-9	Silanetriol, ethyl-, triacetate	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-46-7	Distillates (petroleum), hydrotreated middle	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
75-37-6	1,1-Difluoroethane	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated middle - (64742-46-7)	54.00, Jordanella floridae	68.00, Daphnia magna	Not Available
Methyltriacetoxysilane - (4253-34-3)	501.00, Danio rerio	501.00, Daphnia magna	660.00 (96 hr), Algae
Silanetriol, ethyl-, triacetate - (17689-77-9)	10,000.00, Pimephales promelas	168.70, Daphnia magna	1,200.00 (96 hr), Algae
Cyclotetrasiloxane, octamethyl- - (556-67-2)	200.00, Leuciscus idus	25.20, Daphnia magna	Not Available
1,1-Difluoroethane -(75-37-6)	719.61 Fish		

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Bio Accumulation Factor (BCF): 12,400 flathead minnow (in Cyclotetrasiloxane, octamethyl- < 1%)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1950	UN1950	Not Regulated
14.2. UN proper shipping name	Aerosols, 2.2 LTD QTY	Aerosols, 2.2 LTD QTY	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Aerosols	IMDG: Not Applicable Sub Class: Aerosols	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No;		
14.6. Special precautions for user			
	No further information		

Section 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
US EPA Tier II Hazards	Fire: No Sudden Release of Pressure: Yes Reactive: No Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Safety Data Sheet
RTV Pressurized Silicone Red

SAF-T-LOK

SDS Revision Date:

01/15/2019

International Corporation

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

SDS Revision Date 01/15/19

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H361f Suspected of damaging fertility.

H413 May cause long lasting harmful effects to aquatic life.

Contains gas under pressure.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document